## This Page Is Inserted by IFW Operations and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

## IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

## UK Patent Application GB G2 346 632 GA

(43) Date of A Publication 16.08.2000

- (21) Application No 9930166.5
- (22) Date of Filing 22.12.1999
- (30) Priority Data

(31)	9828234	(32)	22.12.1998	(33)	G8
(31)	9900835	(32)	15.01.1999		
(31)	9923783	(32)	06.10.1999		
/311	9922975	/321	12 10 1000		

(32) 13,10,1999

\_\_\_\_

(31) 9924189

(71) Applicant(s)
Petroline Wellsystems Limited
(Incorporated in the United Kingdom)
Offshore Technology Park, Claymore Drive,
Bridge of Don, ABERDEEN, AB23 &GD,
United Kingdom

Astec Developments Limited
(Incorporated in the United Kingdom)
ODS Building, Greenbank Crescent, East Tullos,
ABERDEEN, AB12 3BG, United Kingdom

- (51) INT CL<sup>7</sup>
  E218 43/10 // E218 33/12
- (52) UK CL (Edition R.) E1F FKA FLA F202 F205
- (56) Documents Cited


  US 6029748 A US 4319393 A US 3948321 A

  US 3712376 A US 3191677 A
- (58) Field of Search

  UK CL (Edition R ) 83J , E1F FJP FKA FLA

  INT CL<sup>7</sup> E218 , E21D

  Online: JAPIO, EPODOC, WPI
- (72) Inventor(s)
  Paul David Metcalle
  Neil Andrew Abercrombie Simpson
- (74) Agent and/or Address for Service
  Cruikshenk & Fairweather
  19 Royal Exchange Square, GLASGOW, G1 3AE,
  United Kingdom
- (54) Abstract Title
  A deformable downhole sealing device
- (57) A method of providing a downhole seal (eg. a packer), in a wellbore, between inner tubing 11 (eg. production tubing) and outer tubing 16 comprises: providing an Intermediate tubing section 18 defining a seal arrangement for engaging with the inner tubing 11. The Intermediate tubing 18 is radially plastically deformed to form an annular extension (40a fig 2). Deformation is achieved via. an expander device 10 comprising a body carrying a plurality of rollers 26. Strips 36 may be included between the deformed zones and the outer tubing to improve the sealing of the expandable tubing 18 to the outer tubing 16. The said extension creates a sealing contact with the outer tubing 16.








Fig. 5




Fig. 1

Fig. 2





Fig. 3

Fig. 4

Fig. 5



٠.

· -

\_

